



AZ 16 ST1-AS R ASI-SAW

- connector plug M12, bottom, 4-pole
- Thermoplastic enclosure
- Long life
- 52 mm x 90 mm x 30 mm
- AS-Interface LED status display
- Actuator coded
- Safety switch with separate actuator
- Integrated AS-Interface
- AS interface M12 Plug-in connection

Data

Ordering data

Product type description	AZ 16 ST1-AS R ASI-SAW
Article number (order number)	101167262
EAN (European Article Number)	4030661218427
eCl@ss number, version 12.0	27-27-26-02
eCl@ss number, version 11.0	27-27-26-02
eCl@ss number, version 9.0	27-27-26-02
ETIM number, version 7.0	EC002592
ETIM number, version 6.0	EC002592

Approvals - Standards

Certificates	cULus ASi-SaW
--------------	------------------

General data

Standards	EN IEC 62026-2 EN ISO 13849-1 EN IEC 60947-5-1 EN IEC 61508
Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Reaction time, maximum	100 ms
Gross weight	115 g

General data - Features

Increased latching force	Yes
Integral system diagnostics, status	Yes

Safety classification

Standards	EN IEC 61508
Performance Level, up to	c
Category	1
PFH value	1.14×10^{-6} /h
Note (PFH-value)	up to max. 100,000 switching cycles/year
Safety Integrity Level (SIL), suitable for applications in	1
Mission time	20 Year(s)

Safety classification - Fault exclusion

Please note:	Can be used when fault exclusion for dangerous damage to the 1-channel mechanism is permissible and sufficient protection against manipulation is guaranteed.
Performance Level, up to	d
Category	3
PFH value	1.01×10^{-7} /h
Note (PFH-value)	up to max. 100,000 switching cycles/year
Safety Integrity Level (SIL), suitable for applications in	2

Mission time	20 Year(s)
--------------	------------

Mechanical data

Mechanical lifetime, minimum	1,000,000 Operations
------------------------------	----------------------

Latching force	30 N
----------------	------

Mechanical data - Connection technique

Connector position	Bottom
--------------------	--------

Termination	Connector plug M12, 4-pole, (A-coding)
-------------	--

Mechanical data - Dimensions

Length of sensor	30 mm
------------------	-------

Width of sensor	52 mm
-----------------	-------

Height of sensor	90 mm
------------------	-------

Ambient conditions

Degree of protection	IP67
----------------------	------

Ambient temperature	-25 ... +60 °C
---------------------	----------------

Storage and transport temperature	-25 ... +85 °C
-----------------------------------	----------------

Protection class	II
------------------	----

Ambient conditions - Insulation values

Rated insulation voltage U_i	32 VDC
--------------------------------	--------

Rated impulse withstand voltage U_{imp}	0.8 kV
---	--------

Overvoltage category	III
----------------------	-----

Degree of pollution	3
---------------------	---

Electrical data

Current consumption	50 mA
---------------------	-------

Electrical data - AS Interface

Rated operating voltage	18 ... 31.6 VDC (Protection against polarity reversal)
-------------------------	--

Electrical data - AS-Interface specification

AS-i Specification	Safety-Slave
AS-i Version	V 2.1
AS-i Profile	S-0.B.F.E
AS-i, IO-Code	0x0
AS-i, ID-Code	0xB
AS-i, ID-Code1	0xF
AS-i, ID-Code2	0xE
AS-i Input, Channel 1	Data bits DI 0 / DI 1 = dynamic code transmission
AS-i Input, Channel 2	Data bits DI 2 / DI 3 = dynamic code transmission
AS-i Parameter bits, P0 ... P3	No function
Note (AS-i Parameter bits)	Set the parameter outputs to "1111" (0xF)
AS-i Input module address	0
Note (AS-i Input module address)	Preset to address 0, can be changed through AS-interface bus master or hand-held programming device

Status indication

Note (LED switching conditions display)	(1) LED green: Supply voltage (2) red LED: Communication error / Slave address = 0 (3) LED yellow : Enabling status
---	---

Pin assignment

PIN 1	AS-i +
PIN 2	n.c.

PIN 3	AS-Interface -
PIN 4	n.c.

Scope of delivery

Scope of delivery	Actuator must be ordered separately.
-------------------	--------------------------------------

Ordering code

Product type description:
AZ 16 (1)-AS (2)

(1)	
ST1	Connector bottom
ST2	Connector right
ST3	Connector left
(2)	
without	Without latching
R	Latching 30 N
R-2254	Latching 5 N


Pictures

Product picture (catalogue individual photo)



ID: kaz16f05
 | 1.3 MB | .jpg | 352.778 x 614.892 mm - 1000 x 1743 px - 72 dpi
 | 85.1 kB | .png | 74.083 x 129.117 mm - 210 x 366 px - 72 dpi
 | 50.4 kB | .jpg | 70.908 x 123.472 mm - 201 x 350 px - 72 dpi
 | 37.4 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi
 | 9.3 MB | .png | 166.474 x 290.31 mm - 1999 x 3486 px - 305 dpi

Dimensional drawing basic component




ID: 1az16g03

| 39.8 kB | .cdr |

| 9.5 kB | .png | 74.083 x 52.211 mm - 210 x 148 px - 72 dpi

| 109.6 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703 px - 72 dpi

Contact arrangement



ID: km12-k4c

| 4.2 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi

| 113.3 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 px - 72 dpi

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 10/02/2026, 13:42